



The ring type assemblies pictured below have the thermocouples embedded either into a stainless steel stamping for grounded junctions (figure 1) or a brass ring for ungrounded junctions (figure 2). Various ring sizes are available to measure the surface temperature of nozzles, extruder barrels, die heads, molds, and many other applicable surfaces.





ORDER CODES

Example Order Number:

JRS1 - F3012

FIGURE 1 1 Grounded Thermocouples - Ring Size

CODE	RING SIZE			SCREW
	I.D. (inches)	W (inches)	L (inches)	or BOLT SIZE
JRS1	0.20	3/8	7/8	#6 - #10 4mm-5mm
JRS2	0.33	7/16	1	#12, 1/4" - 5/16" 5mm - 8mm
JRS3	0.44	9/16	1 1/8	5/16" - 3/8" 8mm - 10mm

FIGURE 2

1 Ungrounded Thermocouples - Ring Size

	CODE	RING SIZE			
		I.D. (inches)	W (inches)	L (inches)	SCREW SIZE
	JRB1U	0.20	3/8	5/8	#6 - #10 4mm-5mm
	JRB2U	0.33	5/8	7/8	#12, 1/4" - 5/16" 5mm - 8mm
	JRB3U	0.44	5/8	7/8	5/16" - 3/8" 8mm - 10mm

Other Element Types

For type E, K, or T thermocouples, replace J in order code with required letter designation.

2 Extension Leadwire "B"

3

CODE ^[1]	DESCRIPTION	
F1	Fiberglass insulation - solid conductor	
F1B	Fiberglass insulation - solid conductor - stainless steel overbraid	
F3	Fiberglass insulation - stranded conductor	
F3B	F3B Fiberglass insulation - stranded conducto	
T1	Teflon® insulation - solid conductor	
T3	Teflon® insulation - stranded conductor	
K1	Kapton® insulation - solid conductor	
[1] Insert 3 digit "B" length in inches. EX: F3B024=24" "B" length.		

3 Terminations and Options

CODE	DESCRIPTION		
0	Leads not stripped		
2	2" split leads, 1/4" stripped		
3	2" split leads with spade lugs		
4	Standard plug		
5	Standard jack		
6	Miniature plug		
7	Miniature jack		
8	2" split leads with 1/4" female disconnect lugs		
О	Options		
MC	Mating connector		
CC	Cable clamp		
ВХ	Box connector		

Kapton® and Teflon® are registered trademarks of E. I. du Pont de Nemours and Company.

